



**SENTINEL**  
SERIES



# THERMOPLASTIC SELF-ALIGNING BALL BEARINGS

Specific design to avoid pollution retention



**WPPL**



**WTBL**



**WNFL**



**WFBL**



**WFPL**

**CF**



**CV**



The protective covers must be ordered separately.  
All bearings are grooved to accommodate the covers.

**SUC**

**PPL**

**204**

**FG1**

## INSERT

**SUC:** Stainless steel insert bearing, fitting on shaft with screws

## HOUSING

**WPPL:** With sole  
**WTBL:** With sole with blind holes  
**WNFL:** Flange bearing with 2 holes  
**WFBL:** Flange bearing with 3 holes  
**WFPL:** Flange bearing with 4 holes  
**W :** Bearing unit prefix only without lubrication system

## DIMENSIONAL

From 204 to 210  
(shaft dia. 20 to 50 mm)

## LUBRICANT

**FG1:** Lubsolid® solid lubrication NSF category H1 certified

For dimensional and technical indications, see the NTN Sentinel Series catalogue <https://www.ntn-snr.com/fr/documents>

This document is the exclusive property of NTN-SNR ROULEMENTS. Any total or partial reproduction hereof without the prior consent of NTN-SNR ROULEMENTS is strictly prohibited. Legal action may be brought against anyone breaching the terms of this paragraph. NTN-SNR ROULEMENTS shall not be held liable for any errors or omissions that may have crept into this document despite the care taken in drafting it. Due to our policy of continuous research and development, we reserve the right to make changes without notice to all or part of the products and specifications mentioned in this document.

© NTN-SNR ROULEMENTS, international copyright 2021.

NTN-SNR ROULEMENTS - 1 rue des Usines - 74000 Anancy - France  
ANNECY Trade and Companies Register B 325 821 072 - APE code 2815 Z - NACE code 28.15  
[www.ntn-snr.com](http://www.ntn-snr.com)

**NTN**






DOC\_L\_THERMO-INOX\_E1\_L\_GBa - Design and production: NTN-SNR Advertising Department © 2021/09 - Photos: © Pedro Studio Photos - Shutterstock.



# STAINLESS STEEL SELF-ALIGNING BEARINGS

The ideal solution to fight humidity



 The protective covers must be ordered separately.  
All bearings are grooved to accommodate the covers.

**SUC P 204 FG1**

## INSERT

**SUC:** Stainless steel insert bearing, fitting on shaft with screws

## HOUSING

**SP:** With sole  
**SPA:** With sole with blind holes  
**SFL:** Flange bearing with 2 holes  
**SFB:** Flange bearing with 3 holes  
**SF:** Flange bearing with 4 holes  
**ST:** Take-up pulleys  
**S:** Bearing unit prefix only in stainless steel

## DIMENSIONAL

From 204 to 210  
(shaft dia. 20 to 50 mm)

## LUBRICANT

**FG1:** Lubsolid® solid lubrication H1 category certified

For dimensional and technical indications, see the NTN Sentinel Series catalogue <https://www.ntn-snr.com/fr/documents>

This document is the exclusive property of NTN-SNR ROULEMENTS. Any total or partial reproduction hereof without the prior consent of NTN-SNR ROULEMENTS is strictly prohibited. Legal action may be brought against anyone breaching the terms of this paragraph. NTN-SNR ROULEMENTS shall not be held liable for any errors or omissions that may have crept into this document despite the care taken in drafting it. Due to our policy of continuous research and development, we reserve the right to make changes without notice to all or part of the products and specifications mentioned in this document.  
© NTN-SNR ROULEMENTS, international copyright 2021.